Confidence intervals (95%) for the amount of moisture lost to evapotranspiration before 100 Tall Fescue entries from data set 22CTFA12 reach 75, 50 and 25% green cover. Entries are ranked based on their ET50 values.

Selection	ET <sub>75</sub>		ET <sub>50</sub>		ET <sub>25</sub>	
PST-5FOE	6.330 to 7.345	6.8	9.448 to 10.16	9.8	12.21 to 13.34	12.8
ATF2190	6.233 to 7.328	6.8	9.395 to 10.17	9.8	12.18 to 13.39	12.8
Easy Green	6.220 to 7.152	6.7	9.300 to 9.957	9.6	12.06 to 13.08	12.6
TALL BOY	6.139 to 7.268	6.7	9.190 to 9.984	9.6	11.86 to 13.08	12.5
ATF2206	5.410 to 6.671	6.0	8.863 to 9.746	9.3	11.87 to 13.26	12.6
ATF1835	5.570 to 7.084	6.3	8.681 to 9.741	9.2	11.30 to 12.90	12.1
PST-5DC320	5.594 to 6.923	6.3	8.665 to 9.595	9.1	11.30 to 12.70	12.0
ATF2047	5.631 to 6.845	6.2	8.642 to 9.491	9.1	11.26 to 12.53	11.9
PST-521DT	5.440 to 6.765	6.1	8.578 to 9.503	9.0	11.28 to 12.67	12.0
ATF1993	5.460 to 6.679	6.1	8.531 to 9.383	9.0	11.21 to 12.48	11.8
PST-5HAF9	5.718 to 6.725	6.2	8.589 to 9.294	8.9	11.14 to 12.18	11.7
PST-5TQBP	6.007 to 6.864	6.4	8.604 to 9.206	8.9	10.94 to 11.81	11.4
PST-520D	5.907 to 6.877	6.4	8.526 to 9.207	8.9	10.85 to 11.83	11.3
SETF221	5.409 to 6.628	6.0	8.438 to 9.289	8.9	11.08 to 12.34	11.7
GLX STAR (PST-5BGG)	5.810 to 6.930	6.4	8.468 to 9.255	8.9	10.79 to 11.92	11.4
PST-5NOG	5.517 to 6.734	6.1	8.404 to 9.256	8.8	10.91 to 12.16	11.5
ATF2059	5.392 to 6.491	5.9	8.315 to 9.084	8.7	10.90 to 12.02	11.5
ATF2035	5.714 to 6.731	6.2	8.323 to 9.037	8.7	10.63 to 11.65	11.1
PST-5LSM	5.454 to 6.447	6.0	8.314 to 9.008	8.7	10.87 to 11.88	11.4
ATF2211	5.324 to 6.494	5.9	8.250 to 9.068	8.7	10.81 to 12.01	11.4
PST-5BP21	5.706 to 6.916	6.3	8.225 to 9.078	8.7	10.39 to 11.60	11.0
DLF-TF/3847	5.624 to 6.538	6.1	8.329 to 8.970	8.7	10.76 to 11.68	11.2
DLF-TF/3840	5.539 to 6.597	6.1	8.276 to 9.018	8.6	10.69 to 11.76	11.2
ATF2205	5.414 to 6.413	5.9	8.290 to 8.989	8.6	10.86 to 11.87	11.4
PST-5CHR	5.390 to 6.464	5.9	8.248 to 8.999	8.6	10.78 to 11.87	11.3
ATF1889	5.312 to 6.457	5.9	8.217 to 9.018	8.6	10.77 to 11.93	11.4
ATF1758	5.300 to 6.607	6.0	8.148 to 9.064	8.6	10.60 to 11.92	11.3
ATF1914	5.210 to 6.510	5.9	8.085 to 8.995	8.5	10.56 to 11.88	11.2
GLX Aced	5.619 to 6.469	6.0	8.234 to 8.831	8.5	10.59 to 11.45	11.0
Lifeguard	5.324 to 6.481	5.9	8.127 to 8.937	8.5	10.58 to 11.75	11.2
SETF320	5.581 to 6.599	6.1	8.142 to 8.858	8.5	10.40 to 11.42	10.9
ATF1736 (Rebel V)	5.327 to 6.348	5.8	8.081 to 8.797	8.4	10.53 to 11.55	11.0
PPG-TF 396	5.540 to 6.350	5.9	8.143 to 8.712	8.4	10.50 to 11.31	10.9
Grande 3	5.470 to 6.273	5.9	8.061 to 8.626	8.3	10.42 to 11.22	10.8
ATF2248	5.463 to 6.571	6.0	7.942 to 8.723	8.3	10.10 to 11.20	10.7
NAI-SOTF22	5.182 to 6.099	5.6	7.986 to 8.628	8.3	10.51 to 11.43	11.0
Rowdier	5.214 to 6.299	5.8	7.924 to 8.685	8.3	10.31 to 11.39	10.9
PPG-TF 423	5.012 to 6.319	5.7	7.831 to 8.746	8.3	10.26 to 11.57	10.9
UGA-19C5	5.082 to 6.081	5.6	7.919 to 8.618	8.3	10.45 to 11.46	11.0
DLF-TF/3850	4.832 to 6.449	5.6	7.698 to 8.831	8.3	10.08 to 11.70	10.9
SETF520	5.127 to 6.072	5.6	7.925 to 8.586	8.3	10.44 to 11.39	10.9
NAI-3BR22	5.037 to 5.974	5.5	7.922 to 8.577	8.2	10.52 to 11.46	11.0
PST-5CHWM	5.024 to 6.069	5.5	7.881 to 8.611	8.2	10.42 to 11.47	11.0

Selection	ET <sub>75</sub>		ET <sub>50</sub>		ET <sub>25</sub>	
ATF1820	5.375 to 6.200	5.8	7.946 to 8.526	8.2	10.28 to 11.10	10.7
NAI-4FRX22	4.756 to 6.188	5.5	7.727 to 8.726	8.2	10.26 to 11.70	11.0
DLF-TF/3849	5.491 to 6.442	6.0	7.877 to 8.549	8.2	9.990 to 10.93	10.5
DLF-TF/3844	5.432 to 6.136	5.8	7.911 to 8.406	8.2	10.18 to 10.88	10.5
ATF1612 (Vert)	5.087 to 6.227	5.7	7.751 to 8.552	8.2	10.08 to 11.21	10.7
PPG-TF 395	5.355 to 6.286	5.8	7.816 to 8.473	8.1	10.01 to 10.93	10.5
PPG-TF 420	5.204 to 6.233	5.7	7.705 to 8.430	8.1	9.907 to 10.93	10.4
PPG-TF 397	5.257 to 6.193	5.7	7.737 to 8.397	8.1	9.945 to 10.87	10.4
ATF1738	4.913 to 6.043	5.5	7.651 to 8.443	8.0	10.05 to 11.18	10.6
PPG-TF 421	5.164 to 6.158	5.7	7.659 to 8.359	8.0	9.866 to 10.85	10.4
UGA-T2	4.986 to 6.065	5.5	7.601 to 8.360	8.0	9.900 to 10.97	10.4
ATF2208	4.852 to 5.705	5.3	7.639 to 8.236	7.9	10.17 to 11.02	10.6
ATF1985	4.632 to 5.772	5.2	7.533 to 8.329	7.9	10.09 to 11.23	10.7
PST-R5HD6	4.448 to 6.065	5.3	7.366 to 8.496	7.9	9.800 to 11.41	10.6
PPG-TF 368	5.208 to 6.020	5.6	7.599 to 8.172	7.9	9.756 to 10.56	10.2
DLF-TF/3843	5.092 to 5.732	5.4	7.656 to 8.106	7.9	10.03 to 10.67	10.4
ATF2054	4.561 to 6.043	5.3	7.321 to 8.362	7.8	9.647 to 11.11	10.4
PST-5CHWT	4.549 to 5.934	5.2	7.297 to 8.268	7.8	9.638 to 11.01	10.3
DLF-TF/3838	4.892 to 5.749	5.3	7.479 to 8.082	7.8	9.817 to 10.66	10.2
Turfway	3.929 to 5.958	4.9	7.052 to 8.462	7.8	9.561 to 11.58	10.6
SETF222	4.154 to 5.692	4.9	7.206 to 8.275	7.7	9.792 to 11.32	10.6
ATF2043	4.646 to 5.594	5.1	7.395 to 8.059	7.7	9.865 to 10.80	10.3
PST-5VFD	4.819 to 5.794	5.3	7.374 to 8.060	7.7	9.647 to 10.61	10.1
Rowdy	4.939 to 6.050	5.5	7.306 to 8.093	7.7	9.357 to 10.45	9.9
ATF2041	4.565 to 5.639	5.1	7.257 to 8.010	7.6	9.636 to 10.69	10.2
DLF-TF/3839	5.056 to 5.723	5.4	7.394 to 7.866	7.6	9.542 to 10.20	9.9
Bladerunner 3	4.718 to 5.856	5.3	7.220 to 8.022	7.6	9.395 to 10.52	10.0
DLF-TF/3848	4.971 to 5.638	5.3	7.348 to 7.818	7.6	9.534 to 10.19	9.9
Raceway	4.956 to 5.778	5.4	7.291 to 7.872	7.6	9.392 to 10.20	9.8
SETF120	4.160 to 5.920	5.0	6.962 to 8.196	7.6	9.250 to 10.99	10.1
DLF-TF/3837	5.012 to 5.736	5.4	7.271 to 7.785	7.5	9.325 to 10.04	9.7
ATF1822	5.080 to 5.894	5.5	7.230 to 7.809	7.5	9.151 to 9.953	9.6
UGA-17F3A	4.519 to 5.586	5.1	7.143 to 7.892	7.5	9.458 to 10.51	10.0
PST-5BVD	4.528 to 5.575	5.1	7.133 to 7.868	7.5	9.434 to 10.46	9.9
UGA-G1	3.979 to 5.464	4.7	6.985 to 8.018	7.5	9.547 to 11.01	10.3
ATF2199	4.675 to 5.544	5.1	7.192 to 7.804	7.5	9.460 to 10.31	9.9
Spyder 2LS	5.007 to 5.705	5.4	7.248 to 7.743	7.5	9.291 to 9.978	9.6
TF 1895 CK	4.769 to 5.702	5.2	7.146 to 7.805	7.5	9.257 to 10.17	9.7
Saltillo	5.222 to 5.946	5.6	7.209 to 7.725	7.5	8.994 to 9.708	9.4
PPG-TF 374	4.889 to 5.674	5.3	7.189 to 7.744	7.5	9.265 to 10.04	9.7
Gazelle II	4.288 to 5.560	4.9	6.958 to 7.851	7.4	9.261 to 10.51	9.9
UGA-18NL1	4.442 to 5.404	4.9	7.061 to 7.736	7.4	9.401 to 10.35	9.9
DLF-TF/3845	4.664 to 5.462	5.1	7.115 to 7.677	7.4	9.337 to 10.12	9.7
ATF2115	4.142 to 5.405	4.8	6.841 to 7.726	7.3	9.173 to 10.41	9.8
ATF2056	4.522 to 5.404	5.0	6.954 to 7.576	7.3	9.135 to 10.00	9.6
DLF-TF/3846	4.361 to 5.337	4.8	6.897 to 7.584	7.2	9.153 to 10.11	9.6
,			•	• •	•	

Selection	ET <sub>75</sub>		ET <sub>50</sub>		ET <sub>25</sub>	
Covenant II	4.322 to 5.315	4.8	6.858 to 7.556	7.2	9.108 to 10.08	9.6
PPG-TF 372	4.628 to 5.581	5.1	6.863 to 7.538	7.2	8.828 to 9.764	9.3
ATF2198	4.282 to 5.216	4.7	6.790 to 7.448	7.1	9.031 to 9.947	9.5
NAI-BNTB22	4.212 to 5.198	4.7	6.764 to 7.457	7.1	9.034 to 9.999	9.5
SR 8700	4.801 to 5.460	5.1	6.839 to 7.308	7.1	8.691 to 9.340	9.0
ATF2207	3.874 to 5.338	4.6	6.552 to 7.578	7.1	8.808 to 10.24	9.5
ATF2048	4.219 to 5.110	4.7	6.731 to 7.358	7.0	8.988 to 9.860	9.4
DLF-TF/3841	4.513 to 5.232	4.9	6.672 to 7.182	6.9	8.629 to 9.336	9.0
ATF2209	4.126 to 5.288	4.7	6.425 to 7.247	6.8	8.395 to 9.534	9.0
NAI-ST822	3.658 to 4.817	4.2	6.269 to 7.080	6.7	8.547 to 9.675	9.1
DLF-TF/3842	3.891 to 5.177	4.5	6.168 to 7.076	6.6	8.081 to 9.339	8.7